

## Safety Data Sheet

### PLANIPREP SC

Safety Data Sheet dated: 5/11/2016 - version 2

Date of first edition: 5/26/2015

## 1. IDENTIFICATION

### Product identifier

Mixture identification:

Trade name: PLANIPREP SC

### Recommended use of the chemical and restrictions on use

Recommended use: Skim coat

Restrictions on use: N.A.

### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive

33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

### Emergency 24 hour numbers:

(USA) CHEMTREC 1-800-424-9300

(Canada) CANUTEC 1-613-996-6666

## 2. HAZARD(S) IDENTIFICATION



### Classification of the chemical

Skin Corr. 1A	Causes severe skin burns and eye damage.
Eye Dam. 1	Causes serious eye damage.
Skin Sens. 1	May cause an allergic skin reaction.
Carc. 1A	May cause cancer if inhaled.

### Label elements

#### Symbols:



Danger

Code	Description
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H350.A	May cause cancer if inhaled.

Code	Description
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260.B	Do not breathe dust.
P264.2	Wash skin thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P302+P352.A	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P310.B	Immediately call a doctor.
P321.A	Specific treatment (see supplementary instructions on this label).

P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P405	Store locked up.
P501.A	Dispose of contents/container in accordance with applicable regulations.

**Ingredient(s) with unknown acute toxicity:**

None

**Hazards not otherwise classified identified during the classification process:**

None

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Substances**

N.A.

**Mixtures**

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

**List of components**

Quantity	Name	Ident. Numb.	Classification
5-10 %	Portland cement	CAS:65997-15-1	STOT SE 3, H335; Eye Dam. 1, H318; Skin Sens. 1, H317; Skin Corr. 1A, H314
2.5-5 %	Slags, ferrous metal, blast furnace	CAS:65996-69-2	Skin Irrit. 2, H315; Eye Dam. 1, H318
0.25-0.49 %	Silica Sand	CAS:14808-60-7	Carc. 1A, H350; STOT RE 1, H372

**4. FIRST AID MEASURES**

**Description of first aid measures**

In case of skin contact:

- Immediately take off all contaminated clothing.
- Obtain medical attention if skin related symptoms persist.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

**Most important symptoms/effects, acute and delayed**

- Eye irritation
- Eye damages
- Skin Irritation
- Erythema

**Indication of any immediate medical attention and special treatment needed**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**5. FIRE-FIGHTING MEASURES**

**Extinguishing media**

Suitable extinguishing media:

- Water.
- Carbon dioxide (CO2).

**Unsuitable extinguishing media:**

None in particular.

**Specific hazards arising from the chemical**

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.
- Hazardous combustion products: N.A.
- Explosive properties: N.A.
- Oxidizing properties: N.A.

**Special protective equipment and precautions for fire-fighters**

- Use suitable breathing apparatus.
- Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
- Move undamaged containers from immediate hazard area if it can be done safely.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

### Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

---

## 7. HANDLING AND STORAGE

### Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

### Conditions for safe storage, including any incompatibilities

Storage temperature: N.A.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

List of components with OEL value

Component	OEL Type	Country	Ceiling	Long Term mg/m <sup>3</sup>	Long Term ppm	Short Term mg/m <sup>3</sup>	Short Term ppm	Behaviour	Note
Portland cement	OSHA			15					
	OSHA			5					
	ACGIH			1					A4 - Not Classifiable as a Human Carcinogen;pulmonary function;respiratory symptoms;asthma;
Silica Sand	ACGIH			0,025					A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis;

Appropriate engineering controls: N.A.

### Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state: Solid

Appearance and colour: Powder whitish

Odour: Cement like

Odour threshold: N.A.

pH in Water Dispersion: 11.50

Melting point / freezing point: N.A.

Initial boiling point and boiling range: N.A.

Flash point: Not Applicable

Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: N.A.  
Solubility in water: Dispersible  
Solubility in oil: N.A.  
Partition coefficient (n-octanol/water): N.A.  
Auto-ignition temperature: N.A.  
Decomposition temperature: N.A.  
Viscosity: N.A.  
Explosive properties: N.A.  
Oxidizing properties: N.A.  
Solid/gas flammability: N.A.

#### **Other information**

Substance groups relevant properties: N.A.  
Miscibility: N.A.  
Fat Solubility: N.A.  
Conductivity: N.A.

---

## **10. STABILITY AND REACTIVITY**

### **Reactivity**

Stable under normal conditions

### **Chemical stability**

Data not Available.

### **Possibility of hazardous reactions**

None.

### **Conditions to avoid**

Stable under normal conditions.

### **Incompatible materials**

None in particular.

### **Hazardous decomposition products**

None.

---

## **11. TOXICOLOGICAL INFORMATION**

### **Information on toxicological effects**

#### **Toxicological information of the mixture:**

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

#### **Toxicological information on main components of the mixture:**

Silica Sand                      a) acute toxicity                      LD50 Oral Rat = 500mg/kg

**If not differently specified, the information required in the regulation and listed below must be considered as N.A.**

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

#### **Substance(s) listed on the IARC Monographs:**

Silica Sand                      Group 1

#### **Substance(s) listed as OSHA Carcinogen(s):**

Silica Sand

#### **Substance(s) listed as NIOSH Carcinogen(s):**

Silica Sand

#### **Substance(s) listed on the NTP report on Carcinogens:**

Silica Sand

## 12. ECOLOGICAL INFORMATION

### Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

#### List of components with eco-toxicological properties

Quantity	Component	Ident. Numb.	Ecotox Infos
0.25-0.49 %	Silica Sand	CAS: 14808-60-7	LC50 a) Aquatic acute toxicity carp> 10000,00000mg/L 72h

### Persistence and degradability

N.A.

### Bioaccumulative potential

N.A.

### Mobility in soil

N.A.

### Other adverse effects

N.A.

---

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

---

## 14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

### UN number

ADR-UN number: N.A.

DOT-UN Number: N.A.

IATA-Un number: N.A.

IMDG-Un number: N.A.

### UN proper shipping name

ADR-Shipping Name: N.A.

DOT-Proper Shipping Name: N.A.

IATA-Technical name: N.A.

IMDG-Technical name: N.A.

### Transport hazard class(es)

ADR-Class: N.A.

DOT-Hazard Class: N.A.

IATA-Class: N.A.

IMDG-Class: N.A.

### Packing group

ADR-Packing Group: N.A.

DOT-Packing group: N.A.

IATA-Packing group: N.A.

IMDG-Packing group: N.A.

### Environmental hazards

Marine pollutant: No

Environmental Pollutant: N.A.

### Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N.A.

### Special precautions

Department of Transportation (DOT):

N.A.

Road and Rail (ADR-RID):

N.A.

Air (IATA):

N.A.

Sea (IMDG):

N.A.

---

## 15. REGULATORY INFORMATION

### USA - Federal regulations

## TSCA - Toxic Substances Control Act

### TSCA inventory:

All the components are listed on the TSCA inventory

### TSCA listed substances:

Portland cement	is listed in TSCA	Section 8b
Slags, ferrous metal, blast furnace	is listed in TSCA	Section 8b
Silica Sand	is listed in TSCA	Section 8b

## SARA - Superfund Amendments and Reauthorization Act

### Section 302 - Extremely Hazardous Substances:

no substances listed

### Section 304 - Hazardous substances:

no substances listed

### Section 313 - Toxic chemical list:

no substances listed

## CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

### Substance(s) listed under CERCLA:

no substances listed

## CAA - Clean Air Act

### CAA listed substances:

no substances listed

## CWA - Clean Water Act

### CWA listed substances:

no substances listed

## USA - State specific regulations

### California Proposition 65

#### Substance(s) listed under California Proposition 65:

Silica Sand	Listed as carcinogen
-------------	----------------------

### Massachusetts Right to know

#### Substance(s) listed under Massachusetts Right to know:

Portland cement  
Silica Sand

### Pennsylvania Right to know

#### Substance(s) listed under Pennsylvania Right to know:

Portland cement  
Silica Sand

### New Jersey Right to know

#### Substance(s) listed under New Jersey Right to know:

Portland cement  
Silica Sand

## Canada- Federal regulations

### DSL - Domestic Substances List

#### DSL Inventory:

All the substances are listed in the DSL.

### NDSL - Non Domestic Substances List

#### NDSL Inventory:

no substances listed

## NPRI - National Pollutant Release Inventory

**Substances listed in NPRI:**


no substances listed

**16. OTHER INFORMATION**

Code	Description
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H350	May cause cancer .
H350.A	May cause cancer if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure .

Safety Data Sheet dated: 5/11/2016 - version 2

Product code: 2762

**Additional classification information**

HMIS Health: 2 = Moderate  
HMIS Health - Is health hazard chronic?: Yes  
HMIS Flammability: 0 = Not Combustible  
HMIS Reactivity: 0 = Minimal  
HMIS P.P.E.: Safety glasses, gloves, dust respirator  
NFPA Health: 2 = Moderate  
NFPA Flammability: 0 = Not Combustible  
NFPA Reactivity: 0 = Minimal  
NFPA Special Risk: N.A.

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

**Legend to abbreviations and acronyms used in the safety data sheet:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.  
IMDG: International Maritime Code for Dangerous Goods.  
IATA: International Air Transport Association.  
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).  
ICAO: International Civil Aviation Organization.  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).  
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.  
CLP: Classification, Labeling, Packaging.  
EINECS: European Inventory of Existing Commercial Chemical Substances.  
INCI: International Nomenclature of Cosmetic Ingredients.  
CAS: Chemical Abstracts Service (division of the American Chemical Society).  
GefStoffVO: Ordinance on Hazardous Substances, Germany.  
LC50: Lethal concentration, for 50 percent of test population.  
LD50: Lethal dose, for 50 percent of test population.  
DNEL: Derived No Effect Level.  
PNEC: Predicted No Effect Concentration.  
TLV: Threshold Limiting Value.  
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).  
STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.

**Paragraphs modified from the previous revision:**

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION



# SAFETY DATA SHEET

## Dec-Tec SBA-100R



Version  
1.1

Revision Date:  
08/29/2016

SDS Number:  
00000605360

---

### SECTION 1. IDENTIFICATION

Product name : Dec-Tec SBA-100R

#### Manufacturer or supplier's details

Company name : Sika Canada Inc.  
601, avenue Delmar  
Pointe-Claire, QC H9R 4A9  
Canada  
www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

Health and Safety Services's  
e-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

#### Recommended use of the chemical and restrictions on use

For further information, refer to product data sheet.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquids : Category 2

Skin irritation : Category 2

Eye irritation : Category 2A

Reproductive toxicity : Category 2

Specific target organ system-  
ic toxicity - single exposure : Category 3 (Central nervous system)

Specific target organ system-  
ic toxicity - repeated expo-  
sure (Inhalation) : Category 2

#### GHS label elements

Hazard pictograms :



# SAFETY DATA SHEET

## Dec-Tec SBA-100R



Version  
1.1

Revision Date:  
08/29/2016

SDS Number:  
000000605360

---

Signal Word	: Danger
Hazard Statements	: H225 Highly flammable liquid and vapor. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
Precautionary Statements	: <b>Prevention:</b> P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. <b>Response:</b> P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. <b>Storage:</b> P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. <b>Disposal:</b> P501 Dispose of contents/ container to an approved waste disposal plant.

Version  
1.1Revision Date:  
08/29/2016SDS Number:  
00000605360**Other hazards**

None known.

**Supplemental information**

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
butanone	78-93-3	>= 30 - < 60
Toluene	108-88-3	>= 10 - < 30
xylene	1330-20-7	>= 1 - < 5
polyvinyl chloride	9002-86-2	>= 1 - < 5

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects  
Respiratory disorder  
Excessive lachrymation  
Erythema  
Dermatitis  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.

# SAFETY DATA SHEET

## Dec-Tec SBA-100R



Version  
1.1

Revision Date:  
08/29/2016

SDS Number:  
00000605360

Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of damaging fertility or the unborn child.  
May cause damage to organs through prolonged or repeated exposure if inhaled.

Notes to physician : Treat symptomatically.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : Water  
High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
- Further information : Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.  
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### SECTION 7. HANDLING AND STORAGE

## SAFETY DATA SHEET

## Dec-Tec SBA-100R

Version  
1.1Revision Date:  
08/29/2016SDS Number:  
000000605360

- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapors or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).  
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Store in original container.  
Store in cool place.  
Keep in a well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butanone	78-93-3	TWA	200 ppm 590 mg/m <sup>3</sup>	CA AB OEL
		STEL	300 ppm 885 mg/m <sup>3</sup>	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWAEV	50 ppm 150 mg/m <sup>3</sup>	CA QC OEL
		STEV	100 ppm 300 mg/m <sup>3</sup>	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
Toluene	108-88-3	TWA	50 ppm 188 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	50 ppm 188 mg/m <sup>3</sup>	CA QC OEL
		TWA	20 ppm	ACGIH
xylene	1330-20-7	TWA	100 ppm 434 mg/m <sup>3</sup>	CA AB OEL

## SAFETY DATA SHEET

## Dec-Tec SBA-100R

Version  
1.1Revision Date:  
08/29/2016SDS Number:  
000000605360

		STEL	150 ppm 651 mg/m <sup>3</sup>	CA AB OEL
		TWAEV	100 ppm 434 mg/m <sup>3</sup>	CA QC OEL
		STEV	150 ppm 651 mg/m <sup>3</sup>	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
ethylbenzene	100-41-4	TWA	100 ppm 434 mg/m <sup>3</sup>	CA AB OEL
		STEL	125 ppm 543 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	100 ppm 434 mg/m <sup>3</sup>	CA QC OEL
		STEV	125 ppm 543 mg/m <sup>3</sup>	CA QC OEL
		TWA	20 ppm	ACGIH
		STEL	125 ppm	ACGIH

**Biological occupational exposure limits**

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
xylene	1330-20-7	Methylhip-puric acids	Urine	End of shift (As soon as	1.5 g/g cre-atinine	ACGIH BEI

## SAFETY DATA SHEET

## Dec-Tec SBA-100R

Version  
1.1Revision Date:  
08/29/2016SDS Number:  
00000605360

				possible after exposure ceases)		
butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
xylene	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

**Engineering measures**

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.  
The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

**Personal protective equipment**

# SAFETY DATA SHEET

## Dec-Tec SBA-100R



Version  
1.1

Revision Date:  
08/29/2016

SDS Number:  
00000605360

- Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection
- Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Remove respiratory and skin/eye protection only after vapors have been cleared from the area.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Wash thoroughly after handling.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : amber
- Odor : characteristic
- Odor Threshold : No data available
- pH : Not applicable
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : 111 °C (232 °F)
- Flash point : ca. -5 °C (23 °F)  
Method: closed cup
- Evaporation rate : No data available



# SAFETY DATA SHEET

## Dec-Tec SBA-100R



Version  
1.1

Revision Date:  
08/29/2016

SDS Number:  
000000605360

---

Flammability (solid, gas)	: No data available
Upper explosion limit	: 7 %(V)
Lower explosion limit	: 1 %(V)
Vapor pressure	: 88.9924 hpa (66.750 mmHg)
Relative vapor density	: No data available
Density	: ca. 0.888 g/cm <sup>3</sup> (23 °C (73 °F) ( ))
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: ca. > 20.5 mm <sup>2</sup> /s (40 °C)
Explosive properties	: No data available
Molecular weight	: No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions. Vapors may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: No data available

No decomposition if stored and applied as directed.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

---

# SAFETY DATA SHEET

## Dec-Tec SBA-100R



Version  
1.1

Revision Date:  
08/29/2016

SDS Number:  
000000605360

### Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 40 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

### Ingredients:

#### **butanone:**

Acute oral toxicity : LD50 Oral (Rat): 3,300 mg/kg

Acute inhalation toxicity : LC50 (Rat): 36 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

#### **Skin corrosion/irritation**

Causes skin irritation.

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Respiratory or skin sensitization**

Skin sensitization: Not classified based on available information.  
Respiratory sensitization: Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **IARC**

Group 2B: Possibly carcinogenic to humans

ethylbenzene

100-41-4

#### **NTP**

Not applicable

#### **Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

#### **STOT-single exposure**

May cause drowsiness or dizziness.

#### **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure if inhaled.

#### **Aspiration toxicity**

Not classified based on available information.

Version  
1.1Revision Date:  
08/29/2016SDS Number:  
000000605360

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

**SECTION 14. TRANSPORT INFORMATION****Domestic regulation****TDG (road/train)**

UN number : UN 1133  
Proper shipping name : ADHESIVES

Class : 3

Packing group : II

Labels : 3

**International Regulations****IATA-DGR**

UN/ID No. : UN 1133  
Proper shipping name : Adhesives

# SAFETY DATA SHEET

## Dec-Tec SBA-100R



Version  
1.1

Revision Date:  
08/29/2016

SDS Number:  
000000605360

Class : 3  
Packing group : II  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

### IMDG-Code

UN number : UN 1133  
Proper shipping name : ADHESIVES

Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-D  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## SECTION 15. REGULATORY INFORMATION

**Canadian PBT Chemicals** : This product contains the following components on the DSL that are classified as Persistent, Bioaccumulative and/or Toxic (PBT) under CEPA:  
Paraffin waxes and Hydrocarbon waxes, chloro

### Canadian lists

No substances are subject to a Significant New Activity Notification.

## SECTION 16. OTHER INFORMATION

Revision Date : 08/29/2016  
Prepared by : R & D of Sika Canada Inc.

### Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

# SAFETY DATA SHEET

## Dec-Tec SBA-100R



Version  
1.1

Revision Date:  
08/29/2016

SDS Number:  
000000605360

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.

### Full text of other abbreviations

ADR	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	Chemical Abstracts Service
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
IATA	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative and toxic
PNEC	Predicted no effect concentration
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

CA / Z8

# SAFETY DATA SHEET

## Dec-Tec SBA-200 VC



Version  
1.1

Revision Date:  
08/29/2016

SDS Number:  
10000000163

### SECTION 1. IDENTIFICATION

Product name : Dec-Tec SBA-200 VC

#### Manufacturer or supplier's details

Company name : Sika Canada Inc.  
601, avenue Delmar  
Pointe-Claire, QC H9R 4A9  
Canada  
www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

Health and Safety Services's  
e-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

#### Recommended use of the chemical and restrictions on use

For further information, refer to product data sheet.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquids : Category 2  
Eye irritation : Category 2A  
Reproductive toxicity : Category 2  
Specific target organ system-  
ic toxicity - single exposure : Category 3 (Central nervous system)

#### GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H361 Suspected of damaging fertility or the unborn child.

Version  
1.1Revision Date:  
08/29/2016SDS Number:  
10000000163

Precautionary Statements : **Prevention:**  
 P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P233 Keep container tightly closed.  
 P240 Ground and bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
 P242 Use non-sparking tools.  
 P243 Take action to prevent static discharges.  
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**  
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P337 + P313 If eye irritation persists: Get medical advice/ attention.  
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**  
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P403 + P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.

**Disposal:**  
 P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**Supplemental information**

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Adhesives

# SAFETY DATA SHEET

## Dec-Tec SBA-200 VC



Version  
1.1

Revision Date:  
08/29/2016

SDS Number:  
10000000163

### Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
acetone	67-64-1	>= 30 - < 60
tert-butyl acetate	540-88-5	>= 30 - < 60
Toluene	108-88-3	>= 0.1 - < 1

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : Respiratory disorder  
Excessive lachrymation  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.  
irritant effects  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of damaging fertility or the unborn child.
- Notes to physician : Treat symptomatically.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : Water  
High volume water jet



Version  
1.1Revision Date:  
08/29/2016SDS Number:  
10000000163

- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
- Further information : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

---

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapors or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Store in original container.

Version  
1.1Revision Date:  
08/29/2016SDS Number:  
10000000163

Store in cool place.  
 Keep in a well-ventilated place.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
 Observe label precautions.  
 Store in accordance with local regulations.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	500 ppm 1,200 mg/m <sup>3</sup>	CA AB OEL
		STEL	750 ppm 1,800 mg/m <sup>3</sup>	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	500 ppm 1,190 mg/m <sup>3</sup>	CA QC OEL
		STEV	1,000 ppm 2,380 mg/m <sup>3</sup>	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
tert-butyl acetate	540-88-5	TWA	200 ppm 950 mg/m <sup>3</sup>	CA AB OEL
		TWA	200 ppm	CA BC OEL
		TWAEV	200 ppm 950 mg/m <sup>3</sup>	CA QC OEL
		TWA	200 ppm	ACGIH
Toluene	108-88-3	TWA	50 ppm 188 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	50 ppm 188 mg/m <sup>3</sup>	CA QC OEL
		TWA	20 ppm	ACGIH

### Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-	0.02 mg/l	ACGIH BEI

Version  
1.1Revision Date:  
08/29/2016SDS Number:  
10000000163

		Toluene	Urine	week End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.  
The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

**Personal protective equipment**

**Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.  
  
The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

**Hand protection**

**Remarks** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

**Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

**Hygiene measures** : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Remove respiratory and skin/eye protection only after vapors

# SAFETY DATA SHEET

## Dec-Tec SBA-200 VC



Version  
1.1

Revision Date:  
08/29/2016

SDS Number:  
10000000163

have been cleared from the area.  
Remove contaminated clothing and protective equipment  
before entering eating areas.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: viscous
Color	: milky, off-white
Odor	: acetone-like
Odor Threshold	: No data available
pH	: Not applicable
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: ca. 56 °C (133 °F)
Flash point	: -20 °C (-4 °F) Method: closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 13 %(V)
Lower explosion limit	: 2.5 %(V)
Vapor pressure	: 2.3298 hpa (1.747 mmHg)
Relative vapor density	: No data available
Density	: ca. 0.88 g/cm <sup>3</sup> (23 °C (73 °F) ( ))
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: ca. > 20.5 mm <sup>2</sup> /s (40 °C)

# SAFETY DATA SHEET

## Dec-Tec SBA-200 VC



Version  
1.1

Revision Date:  
08/29/2016

SDS Number:  
10000000163

---

Explosive properties : No data available  
Molecular weight : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.  
Chemical stability : The product is chemically stable.  
Possibility of hazardous reactions : Stable under recommended storage conditions.  
Vapors may form explosive mixture with air.  
Conditions to avoid : Heat, flames and sparks.  
Incompatible materials : No data available  
No decomposition if stored and applied as directed.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Ingredients:

##### acetone:

Acute oral toxicity : LD50 Oral (Rat): 5,800 mg/kg  
Acute inhalation toxicity : LC50 (Rat): 76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Acute dermal toxicity : LD50 Dermal (Rabbit): 20,000 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.  
Respiratory sensitization: Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.  
**IARC** Not applicable

**NTP** Not applicable

Version  
1.1Revision Date:  
08/29/2016SDS Number:  
10000000163**Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

**STOT-single exposure**

May cause drowsiness or dizziness.

**STOT-repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Ingredients:****acetone:**

- |   |   |  |
|---|---|--|
| Toxicity to fish                                    | : | LC50 (Fish): > 5,000 mg/l<br>Exposure time: 96 h   |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia): 12.700 mg/l<br>Exposure time: 48 h                                       |
| Toxicity to algae                                   | : | ErC50 (Pseudokirchneriella subcapitata (green algae)): > 530 mg/l<br>Exposure time: 96 h |

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects****Product:**

- |                                   |   |  |
|-----------------------------------|---|--|
| Additional ecological information | : | Do not empty into drains; dispose of this material and its container in a safe way.<br>Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. |
|-----------------------------------|---|--|

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

- |                     |   |  |
|---------------------|---|--|
| Waste from residues | : | Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. |
|---------------------|---|--|

# SAFETY DATA SHEET

## Dec-Tec SBA-200 VC



Version  
1.1

Revision Date:  
08/29/2016

SDS Number:  
10000000163

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

### SECTION 14. TRANSPORT INFORMATION

#### Domestic regulation

##### TDG (road/train)

UN number : UN 1133  
Proper shipping name : ADHESIVES  
  
Class : 3  
Packing group : II  
Labels : 3

#### International Regulations

##### IATA-DGR

UN/ID No. : UN 1133  
Proper shipping name : Adhesives  
Class : 3  
Packing group : II  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

##### IMDG-Code

UN number : UN 1133  
Proper shipping name : ADHESIVES  
  
Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-D  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### SECTION 15. REGULATORY INFORMATION

**Canadian PBT Chemicals** : This product contains the following components on the DSL that are classified as Persistent, Bioaccumulative and/or Toxic (PBT) under CEPA:  
Paraffin waxes and Hydrocarbon waxes, chloro

#### Canadian lists

No substances are subject to a Significant New Activity Notification.

# SAFETY DATA SHEET

## Dec-Tec SBA-200 VC



Version  
1.1

Revision Date:  
08/29/2016

SDS Number:  
10000000163

---

### SECTION 16. OTHER INFORMATION

Revision Date : 08/29/2016  
Prepared by : R & D of Sika Canada Inc.

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.

#### Full text of other abbreviations

ADR	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	Chemical Abstracts Service
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
IATA	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative and toxic
PNEC	Predicted no effect concentration
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

CA / Z8



## Safety Data Sheet

### DEC-TEC WBA100

Safety Data Sheet dated: 4/5/2016 - version 2

Date of first edition: 4/21/2015

## 1. IDENTIFICATION

### Product identifier

Mixture identification:

Trade name: DEC-TEC WBA100

### Recommended use of the chemical and restrictions on use

Recommended use: Adhesive

Restrictions on use: N.A.

### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive

33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

### Emergency 24 hour numbers:

(USA) CHEMTREC 1-800-424-9300

(Canada) CANUTEC 1-613-996-6666

## 2. HAZARD(S) IDENTIFICATION



### Classification of the chemical

Muta. 1B May cause genetic defects if inhaled.

Carc. 1B May cause cancer if inhaled.

### Label elements

#### Symbols:



Danger

Code	Description
------	-------------

H340.A	May cause genetic defects if inhaled.
--------	---------------------------------------

H350.A	May cause cancer if inhaled.
--------	------------------------------

Code	Description
------	-------------

P201	Obtain special instructions before use.
------	---

P202	Do not handle until all safety precautions have been read and understood.
------	---

P280	Wear protective gloves/protective clothing/eye protection/face protection.
------	--

P308+P313	IF exposed or concerned: Get medical advice/attention.
-----------	--

P405	Store locked up.
------	------------------

P501.A	Dispose of contents/container in accordance with applicable regulations.
--------	--

### Ingredient(s) with unknown acute toxicity:

None

### Hazards not otherwise classified identified during the classification process:

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Substances

N.A.

### Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

**List of components**

Quantity	Name	Ident. Numb.	Classification
0.49-1 %	Naphthenic oil	CAS:64742-95-6	Asp. Tox. 1, H304; Muta. 1B, H340; Carc. 1B, H350; Flam. Liq. 3, H226
0.25-0.49 %	Silica Sand	CAS:14808-60-7	Carc. 1A, H350.A; STOT RE 1, H372.A
0.1-0.25 %	Vinyl acetate	CAS:108-05-4	Flam. Liq. 2, H225; Acute Tox. 4, H332; Carc. 2, H351; STOT SE 3, H335; Aquatic Chronic 3, H412

---

#### 4. FIRST AID MEASURES

##### Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

##### Most important symptoms/effects, acute and delayed

N.A.

##### Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

---

#### 5. FIRE-FIGHTING MEASURES

##### Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO<sub>2</sub>).

##### Unsuitable extinguishing media:

None in particular.

##### Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: N.A.

Explosive properties: N.A.

Oxidizing properties: N.A.

##### Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

##### Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

---

#### 7. HANDLING AND STORAGE

##### Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

### Conditions for safe storage, including any incompatibilities

Storage temperature: N.A.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### List of components with OEL value

Component	OEL Type	Country	Ceiling	Long Term mg/m <sup>3</sup>	Long Term ppm	Short Term mg/m <sup>3</sup>	Short Term ppm	Behaviour	Note
Silica Sand	ACGIH			0,025					A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis;
Vinyl acetate	ACGIH				10		15		A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans;CNS impairment;eye, skin and upper respiratory tract irritation;
	EU			17,6	5	35,2	10	Indicative	

Appropriate engineering controls: N.A.

### Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: Paste

Odour: Latex like

Odour threshold: N.A.

pH: 9.00

Melting point / freezing point: N.A.

Initial boiling point and boiling range: N.A.

Flash point: >93,3 °C (199,9 °F)

Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: N.A.

Solubility in water: N.A.

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Viscosity: N.A.

Explosive properties: N.A.

Oxidizing properties: N.A.

Solid/gas flammability: N.A.

### Other information

Substance groups relevant properties: N.A.

Miscibility: N.A.

Fat Solubility: N.A.

Conductivity: N.A.

---

## 10. STABILITY AND REACTIVITY

**Reactivity**

Stable under normal conditions

**Chemical stability**

Data not Available.

**Possibility of hazardous reactions**

None.

**Conditions to avoid**

Stable under normal conditions.

**Incompatible materials**

None in particular.

**Hazardous decomposition products**

None.

**11. TOXICOLOGICAL INFORMATION****Information on toxicological effects****Toxicological information of the mixture:**

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

**Toxicological information on main components of the mixture:**

Naphthenic oil	a) acute toxicity	LD50 Skin Rabbit > 2000mg/kg LC50 Inhalation Rat = 3400ppm 4h
Silica Sand	a) acute toxicity	LD50 Oral Rat = 500mg/kg
Vinyl acetate	a) acute toxicity	LD50 Skin Rabbit = 2320mg/kg LC50 Inhalation Rat = 11400mg/m3 4h LD50 Oral Rat = 2920mg/kg

If not differently specified, the information required in the regulation and listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

**Substance(s) listed on the IARC Monographs:**

Silica Sand	Group 1
Vinyl acetate	Group 2B

**Substance(s) listed as OSHA Carcinogen(s):**

Silica Sand  
Vinyl acetate

**Substance(s) listed as NIOSH Carcinogen(s):**

Silica Sand

**Substance(s) listed on the NTP report on Carcinogens:**

Silica Sand

**12. ECOLOGICAL INFORMATION****Toxicity**

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

**List of components with eco-toxicological properties**

Quantity	Component	Ident. Numb.	Ecotox Infos
Date	4/5/2016	Production Name	DEC-TEC WBA100

0.49-1 %	Naphthenic oil	CAS: 64742-95-6	LC50 a) Aquatic acute toxicity Fish Oncorhynchus mykiss= 922mg/L 96h IUCLID EC50 a) Aquatic acute toxicity Daphnia Daphnia magna= 614mg/L 48h IUCLID LC50 G 5 Colinus virginianus> 6500ppm 5d IUCLID LD50 G 5 Colinus virginianus> 2250mg/kg IUCLID
0.25-0.49 %	Silica Sand	CAS: 14808-60-7	LC50 a) Aquatic acute toxicity carp> 10000,00000mg/L 72h
0.1-0.25 %	Vinyl acetate	CAS: 108-05-4	LC50 a) Aquatic acute toxicity Fish Pimephales promelas= 14mg/L 96h EPA LC50 a) Aquatic acute toxicity Fish Lepomis macrochirus1504mg/L 96h EPA LC50 a) Aquatic acute toxicity Fish Poecilia reticulata261mg/L 96h EPA

**Persistence and degradability**

N.A.

**Bioaccumulative potential**

N.A.

**Mobility in soil**

N.A.

**Other adverse effects**

N.A.

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

**14. TRANSPORT INFORMATION**

**UN number**

ADR-UN number: N/A  
DOT-UN Number: N/A  
IATA-Un number: N/A  
IMDG-Un number: N/A

**UN proper shipping name**

ADR-Shipping Name: N/A  
DOT-Proper Shipping Name: N/A  
IATA-Technical name: N/A  
IMDG-Technical name: N/A

**Transport hazard class(es)**

ADR-Class: N/A  
DOT-Hazard Class: N/A  
IATA-Class: N/A  
IMDG-Class: N/A

**Packing group**

ADR-Packing Group: N/A  
DOT-Packing group: N/A  
IATA-Packing group: N/A  
IMDG-Packing group: N/A

**Environmental hazards**

Marine pollutant: No  
Environmental Pollutant: N.A.

**Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

N.A.

**Special precautions**

Department of Transportation (DOT):  
DOT-Special Provision(s): N/A  
DOT-Label(s): N/A  
DOT-Symbol: N/A  
DOT-Cargo Aircraft: N/A  
DOT-Passenger Aircraft: N/A  
DOT-Bulk: N/A  
DOT-Non-Bulk: N/A  
Road and Rail (ADR-RID):  
ADR-Label: N/A  
ADR-Hazard identification number: N/A

ADR-Tunnel Restriction Code: N/A

**Air (IATA):**

IATA-Passenger Aircraft: N/A  
IATA-Cargo Aircraft: N/A  
IATA-Label: N/A  
IATA-Subrisk: N/A  
IATA-Erg: N/A  
IATA-Special Provisions: N/A

**Sea (IMDG):**

IMDG-Stowage Code: N/A  
IMDG-Stowage Note: N/A  
IMDG-Subrisk: N/A  
IMDG-Special Provisions: N/A  
IMDG-Page: N/A  
IMDG-Label: N/A  
IMDG-EMS: N/A  
IMDG-MFAG: N/A

**15. REGULATORY INFORMATION**

**USA - Federal regulations**

**TSCA - Toxic Substances Control Act**

**TSCA inventory:**

All the components are listed on the TSCA inventory

**TSCA listed substances:**

Naphthenic oil	is listed in TSCA	Section 8b
Silica Sand	is listed in TSCA	Section 8b
Vinyl acetate	is listed in TSCA	Section 8b

**SARA - Superfund Amendments and Reauthorization Act**

**Section 302 - Extremely Hazardous Substances:**

Vinyl acetate

**Section 304 - Hazardous substances:**

Vinyl acetate

**Section 313 - Toxic chemical list:**

Vinyl acetate

**CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act**

**Substance(s) listed under CERCLA:**

Vinyl acetate	Reportable quantity:	5000	pounds
---------------	----------------------	------	--------

**CAA - Clean Air Act**

**CAA listed substances:**

Vinyl acetate	is listed in CAA	Section 112(b) - HAP, Section 112(b) - HON
---------------	------------------	--

**CWA - Clean Water Act**

**CWA listed substances:**

Vinyl acetate	is listed in CWA	Section 311
---------------	------------------	-------------

**USA - State specific regulations**

**California Proposition 65**

**Substance(s) listed under California Proposition 65:**

Silica Sand	Listed as carcinogen
-------------	----------------------

**Massachusetts Right to know**

**Substance(s) listed under Massachusetts Right to know:**

Silica Sand  
Vinyl acetate

**Pennsylvania Right to know**

**Substance(s) listed under Pennsylvania Right to know:**

Silica Sand  
Vinyl acetate

**New Jersey Right to know**

**Substance(s) listed under New Jersey Right to know:**

Silica Sand  
Vinyl acetate

**Canada- Federal regulations**

**DSL - Domestic Substances List**

**DSL Inventory:**

All the substances are listed in the DSL.

**NDSL - Non Domestic Substances List**

**NDSL Inventory:**

no substances listed

**NPRI - National Pollutant Release Inventory**

**Substances listed in NPRI:**

no substances listed

---


**16. OTHER INFORMATION**

Code	Description
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H340	May cause genetic defects .
H340.A	May cause genetic defects if inhaled.
H350	May cause cancer .
H350.A	May cause cancer if inhaled.
H351	Suspected of causing cancer .
H372.A	Causes damage to organs through prolonged or repeated exposure if inhaled.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet dated: 4/5/2016 - version 2

Product code: 3253

**Additional classification information**



HMIS Health: 1 = Slight

HMIS Health - Is health hazard chronic?: Yes

HMIS Flammability: 1 = Combustible if heated

HMIS Reactivity: 0 = Minimal

HMIS P.P.E.: Safety glasses, gloves

NFPA Health: 1 = Slight

NFPA Flammability: 1 = Combustible if heated

NFPA Reactivity: 0 = Minimal

NFPA Special Risk: NONE

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial,

and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

**Legend to abbreviations and acronyms used in the safety data sheet:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.  
IMDG: International Maritime Code for Dangerous Goods.  
IATA: International Air Transport Association.  
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).  
ICAO: International Civil Aviation Organization.  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).  
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.  
CLP: Classification, Labeling, Packaging.  
EINECS: European Inventory of Existing Commercial Chemical Substances.  
INCI: International Nomenclature of Cosmetic Ingredients.  
CAS: Chemical Abstracts Service (division of the American Chemical Society).  
GefStoffVO: Ordinance on Hazardous Substances, Germany.  
LC50: Lethal concentration, for 50 percent of test population.  
LD50: Lethal dose, for 50 percent of test population.  
DNEL: Derived No Effect Level.  
PNEC: Predicted No Effect Concentration.  
TLV: Threshold Limiting Value.  
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).  
STEL: Short Term Exposure limit.  
STOT: Specific Target Organ Toxicity.  
WGK: German Water Hazard Class.  
KSt: Explosion coefficient.

**Paragraphs modified from the previous revision:**

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 4. FIRST AID MEASURES
- 7. HANDLING AND STORAGE
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION