

# SAFETY DATA SHEET

## Dec-Tec SBA-200 VC



Version  
1.2

Revision Date:  
01/03/2017

SDS Number:  
10000000163

### SECTION 1. IDENTIFICATION

Product name : Dec-Tec SBA-200 VC

#### Manufacturer or supplier's details

Company name : Sika Canada Inc.  
601, avenue Delmar  
Pointe-Claire, QC H9R 4A9  
Canada  
www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

Health and Safety Services's  
e-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

#### Recommended use of the chemical and restrictions on use

For further information, refer to product data sheet.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquids : Category 2

Eye irritation : Category 2A

Reproductive toxicity : Category 2

Effects on or via lactation

Specific target organ system-  
ic toxicity - single exposure : Category 3 (Central nervous system)

#### GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.  
H319 Causes serious eye irritation.

# SAFETY DATA SHEET

## Dec-Tec SBA-200 VC



Version  
1.2

Revision Date:  
01/03/2017

SDS Number:  
10000000163

- H336 May cause drowsiness or dizziness.  
H361 Suspected of damaging fertility or the unborn child.  
H362 May cause harm to breast-fed children.
- Precautionary Statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
P263 Avoid contact during pregnancy and while nursing.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
- Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
- Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.
- Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.
- Warning : Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain, liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

### Other hazards

# SAFETY DATA SHEET

## Dec-Tec SBA-200 VC



Version  
1.2

Revision Date:  
01/03/2017

SDS Number:  
10000000163

None known.

### Supplemental information

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
acetone	67-64-1	$\geq 30$ - $< 40$
Alkane, C14-17-, chloro-	85535-85-9	$\geq 0$ - $< 1$
Toluene	108-88-3	$\geq 0$ - $< 1$

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : Respiratory disorder  
Excessive lachrymation  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.  
irritant effects  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of damaging fertility or the unborn child.  
May cause harm to breast-fed children.
- Notes to physician : Treat symptomatically.

Version  
1.2Revision Date:  
01/03/2017SDS Number:  
10000000163

---

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : Water  
High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
- Further information : Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.  
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

---

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapors or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.

Version  
1.2Revision Date:  
01/03/2017SDS Number:  
10000000163

For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).  
Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Store in original container.  
Store in cool place.  
Keep in a well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	500 ppm 1,200 mg/m <sup>3</sup>	CA AB OEL
		STEL	750 ppm 1,800 mg/m <sup>3</sup>	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	500 ppm 1,190 mg/m <sup>3</sup>	CA QC OEL
		STEV	1,000 ppm 2,380 mg/m <sup>3</sup>	CA QC OEL
tert-butyl acetate	540-88-5	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	200 ppm 950 mg/m <sup>3</sup>	CA AB OEL
		TWA	200 ppm	CA BC OEL
		TWAEV	200 ppm 950 mg/m <sup>3</sup>	CA QC OEL
Toluene	108-88-3	TWA	200 ppm	ACGIH
		TWA	50 ppm 188 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	50 ppm 188 mg/m <sup>3</sup>	CA QC OEL
		TWA	20 ppm	ACGIH

Version  
1.2Revision Date:  
01/03/2017SDS Number:  
10000000163**Biological occupational exposure limits**

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI

**Engineering measures**

- : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
- The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

**Personal protective equipment**

## Respiratory protection

- : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

## Hand protection

## Remarks

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling

# SAFETY DATA SHEET

## Dec-Tec SBA-200 VC



Version  
1.2

Revision Date:  
01/03/2017

SDS Number:  
10000000163

---

	chemical products if a risk assessment indicates this is necessary.
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Hygiene measures	: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove respiratory and skin/eye protection only after vapors have been cleared from the area. Remove contaminated clothing and protective equipment before entering eating areas.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: viscous
Color	: milky, off-white
Odor	: acetone-like
Odor Threshold	: No data available
pH	: Not applicable
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: ca. 56 °C (133 °F)
Flash point	: -20 °C (-4 °F) Method: closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 13 %(V)
Lower explosion limit	: 2.5 %(V)
Vapor pressure	: 2.3298 hpa (1.747 mmHg)
Relative vapor density	: No data available
Density	: ca. 0.88 g/cm <sup>3</sup> (23 °C (73 °F) (l))
Solubility(ies)	

# SAFETY DATA SHEET

## Dec-Tec SBA-200 VC



Version  
1.2

Revision Date:  
01/03/2017

SDS Number:  
10000000163

---

Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: ca. > 20.5 mm <sup>2</sup> /s (40 °C)
Explosive properties	: No data available
Molecular weight	: No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions. Vapors may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: No data available
No decomposition if stored and applied as directed.	

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Ingredients:

##### acetone:

Acute oral toxicity	: LD50 Oral (Rat): 5,800 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 76 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	: LD50 Dermal (Rabbit): 20,000 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.



Version  
1.2Revision Date:  
01/03/2017SDS Number:  
10000000163**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory or skin sensitization**

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**IARC** Not applicable**NTP** Not applicable**Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

May cause harm to breast-fed children.

**STOT-single exposure**

May cause drowsiness or dizziness.

**STOT-repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Ingredients:****acetone:**Toxicity to fish : LC50 (Fish): > 5,000 mg/l  
Exposure time: 96 hToxicity to daphnia and other : EC50 (Daphnia): 12.700 mg/l  
aquatic invertebrates Exposure time: 48 hToxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 530  
mg/l  
Exposure time: 96 h**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

Version  
1.2Revision Date:  
01/03/2017SDS Number:  
10000000163**Other adverse effects****Product:**

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

**SECTION 14. TRANSPORT INFORMATION****Domestic regulation****TDG (road/train)**

UN number : UN 1133  
Proper shipping name : ADHESIVES

Class : 3  
Packing group : II  
Labels : 3

**International Regulations****IATA-DGR**

UN/ID No. : UN 1133  
Proper shipping name : Adhesives  
Class : 3  
Packing group : II  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

**IMDG-Code**

UN number : UN 1133  
Proper shipping name : ADHESIVES

Class : 3  
Packing group : II  
Labels : 3

# SAFETY DATA SHEET

## Dec-Tec SBA-200 VC



Version  
1.2

Revision Date:  
01/03/2017

SDS Number:  
10000000163

EmS Code : F-E, S-D  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## SECTION 15. REGULATORY INFORMATION

**Canadian PBT Chemicals** : This product contains the following components on the DSL that are classified as Persistent, Bioaccumulative and/or Toxic (PBT) under CEPA:  
Alkane, C14-17-, chloro-

### Canadian lists

No substances are subject to a Significant New Activity Notification.

## SECTION 16. OTHER INFORMATION

Revision Date : 01/03/2017  
Prepared by : R & D of Sika Canada Inc.

### Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.

### Full text of other abbreviations

ADR	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	Chemical Abstracts Service
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
IATA	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in air that

# SAFETY DATA SHEET

## Dec-Tec SBA-200 VC



Version  
1.2

Revision Date:  
01/03/2017

SDS Number:  
10000000163

---

MARPOL	kills 50% of the test animals during the observation period) International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative and toxic
PNEC	Predicted no effect concentration
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

CA / Z8