



# Dec-Clad Kickout

## CRITICAL LEAK POINT PROTECTION

### THE PRODUCT ADVANTAGE

Dec-Clad Kickout is the recommended termination method anywhere where it is impossible or impractical to get the membrane up and under a finished surface of a wall.

There are 3 typical applications for this procedure,

- Vertical Concrete surfaces
- Vertical Brick surfaces
- Vertical Block surfaces

Dec-Clad Kickout introduces one of the easiest and most efficient ways to terminate Dec-Tec membrane to vertical surfaces. Dec-Clad Kickout is fastened directly to an existing (finished) wall and the membrane is thermally heat welded to it. Dec-Tec sealant (Tremco 830) is then added between the top of the Kickout and wall to ensure waterproofing and a great aesthetic finish.

### FEATURES:

1. PVC coated G90 galvanized steel
2. Welded terminations ensuring a watertight solution.
3. Color coordinated patterns and colors to compliment all Dec-Tec membranes.
4. Colors: Granite, Bronze, Brick, Solid Grey, CoolStep White, Brown and Black
5. Available in 8' long lengths, easily cut and fit on site.
6. Standard dimensions: 3" x 1/2" x 1/2"

### PACKAGING:

1. Standard dimensions:
  - 3" x 1/2" x 1/2" » 8' long
  - 7.62 cm x 1.27 cm x 1.27 cm » 2.44 m long
2. All lengths are 8' (2.44 m)

For additional information please call our toll-free number:

**1-866-461-3914**